

# Xerox® VersaLink® C600 Colour Printer

VersaLink® C600 Colour Printers are built on Xerox® ConnectKey® Technology.  
For more information, go to [www.connectkey.co.uk](http://www.connectkey.co.uk).



| SYSTEM SPECIFICATIONS   | VERSALINK® 600   |
|---|--|
| <b>One-sided Speed<sup>1</sup></b><br>216 x 279 mm<br>A4/210 x 297 mm<br>216 x 356 mm | Up to 55 ppm colour and black-and-white<br>Up to 53 ppm colour and black-and-white<br>Up to 45 ppm colour and black-and-white  |
| <b>Two-sided Speed<sup>1</sup></b><br>216 x 279 mm<br>A4/210 x 297 mm<br>216 x 356 mm | Up to 52 ppm colour and black-and-white<br>Up to 50 ppm colour and black-and-white<br>Up to 26 ppm colour and black-and-white  |
| <b>Monthly Duty Cycle<sup>2</sup></b>   | Up to 120,000 pages/month  |
| <b>Recommended Average Monthly Print Volume<sup>3</sup></b>                           | Up to 17,000 pages   |
| <b>Hard Drive</b>   | Optional 320 GB HDD  |
| <b>Processor</b>  | 1.05 GHz ARM Dual-Core   |
| <b>Memory</b>   | 2 GB   |
| <b>Connectivity</b>   | Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair   |
| <b>Controller Features</b>  | Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support |
| <b>User Interface Languages</b>   | English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian                       |

| DEVICE SPECIFICATIONS                            |  |          |          |         |
|--|--|----------|----------|---------|
| ELECTRICAL REQUIREMENTS                          |  |          |          |         |
| North America                                    | Voltage: 110-127V +/-10%<br>Frequency: 50/60 Hz +/-3%, 12A |          |          |         |
| Europe and Other Geographies                     | Voltage: 220-240V +/- 10%<br>Frequency: 50/60 Hz +/-3%, 8A |          |          |         |
| POWER CONSUMPTION                                |  |          |          |         |
| Continuous Printing <sup>4</sup>                 | 800 watts or less  |          |          |         |
| Ready/Standby Mode <sup>4</sup>                  | 85 watts or less   |          |          |         |
| Energy Saver/Sleep Mode <sup>4</sup>             | 0.7 watts or less  |          |          |         |
| OPERATING ENVIRONMENT                            |  |          |          |         |
| Required Temperature Range (Storage)             | 0° to 35° C (32° to 95° F)                                 |          |          |         |
| Required Temperature Range (Operating)           | 10° to 32° C (50° to 90° F)                                |          |          |         |
| Required Relative Humidity                       | 15% to 85%   |          |          |         |
| Sound Power Levels<br>Operating<br>Standby       | 7.27 B(A) or less<br>4.84 B(A) or less                     |          |          |         |
| Sound Pressure Levels<br>Operating<br>Standby    | 57.4 dB(A) or less<br>33.5 dB(A) or less                   |          |          |         |
| Boot Time (from Off to UI Ready)                 | As fast as 52 seconds                                      |          |          |         |
| Warm-up Time (from Sleep to UI Ready)            | As fast as 11 seconds                                      |          |          |         |
| DIMENSIONS AND WEIGHT (UNPACKAGED)               | WIDTH  | DEPTH    | HEIGHT   | WEIGHT  |
| Base Unit  | 427.4 mm   | 465.5 mm | 443.4 mm | 29.4 kg |
| Base Unit with Additional 550-sheet Tray         | 427.4 mm   | 465.5 mm | 566.4 mm | 36 kg   |
| Base Unit with High-Capacity Feeder              | 724.2 mm   | 772.1 mm | 902.4 mm | 49.1 kg |
| Base Unit with High-Capacity Feeder and Finisher | 724.2 mm   | 772.1 mm | 1121 mm  | 55.9 kg |
| Base Unit with High-Capacity Feeder and Mailbox  | 724.2 mm   | 772.1 mm | 1121 mm  | 54.4 kg |
| 550-sheet Paper Tray                             | 420 mm   | 464.5 mm | 123 mm   | 6.6 kg  |
| High-Capacity Feeder (includes Caster Base)      | 724.2 mm   | 772.1 mm | 459 mm   | 19.7 kg |
| Cabinet (includes Caster Base)                   | 724.2 mm   | 772.1 mm | 336 mm   | 16.6 kg |
| Caster Base                                      | 724.2 mm   | 772.1 mm | 90 mm    | 8.5 kg  |
| Mailbox  | 450.8 mm   | 477.6 mm | 248.0 mm | 5.3 kg  |
| Finisher   | 450.8 mm   | 411.0 mm | 248.0 mm | 6.8 kg  |

# Xerox® VersaLink® C600 Color Printer

| <b>DIMENSIONS AND WEIGHT (PACKAGED)</b>     | <b>WIDTH</b>  | <b>DEPTH</b> | <b>HEIGHT</b> | <b>WEIGHT</b> |
|---|---|--------------|---------------|---------------|
| Base Unit                                   | 580 mm  | 634 mm       | 607 mm        | 35 kg         |
| 550-sheet Paper Tray                        | 535 mm  | 584 mm       | 248 mm        | 8.5 kg        |
| High-Capacity Feeder (includes Caster Base) | 568 mm  | 663 mm       | 711 mm        | 38 kg         |
| Cabinet (includes Caster Base)              | 584 mm  | 629 mm       | 597 mm        | 28 kg         |
| Caster Base                                 | 585 mm  | 619 mm       | 330 mm        | 18 kg         |
| Mailbox                                     | 573 mm  | 518 mm       | 386 mm        | 7.8 kg        |
| Finisher                                    | 573 mm  | 398 mm       | 386 mm        | 8.8 kg        |
| <b>CERTIFICATIONS</b>                       |   |              |               |               |
|   | To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .   |              |               |               |
| <b>PRINT</b>                                |   |              |               |               |
| First-Print-Out Time                        | As fast as 5.1 seconds colour/4.7 seconds black-and-white   |              |               |               |
| Print Resolution                            | Up to 1200 x 2400 dpi   |              |               |               |
| Page Description Languages                  | PCL® 5e, 6<br>PDF<br>XPS<br>TIFF<br>JPEG<br>HP-GL<br>Adobe® PostScript® 3™  |              |               |               |
| Maximum Print Area                          | 4 mm from edge of paper   |              |               |               |
| Print Features                              | <ul style="list-style-type: none"> <li>Application Defaults</li> <li>Banner Pages Enable/Disable</li> <li>Bi-directional Real-time Status</li> <li>Booklet Layout</li> <li>Colour Adjustments (lightness, contrast, saturation, colour balance)</li> <li>Colour Correction</li> <li>Draft Mode</li> <li>Fit to New Paper Size</li> <li>Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)</li> <li>Job Monitoring (Client or Local User Interface)</li> <li>N-up Page Layout (up to 16 pages per sheet)</li> <li>Paper Selection by Attribute</li> <li>Personal Print</li> <li>Print Around Enable/Disable</li> <li>Print from USB</li> <li>Run Black</li> <li>Sample Set</li> <li>Saved Job</li> <li>Scaling</li> <li>Secure Print</li> <li>Skip Blank Pages</li> <li>Special Pages (exception page programming covers, inserts, exceptions pages)</li> <li>Store and Recall Driver Settings</li> <li>Stored Jobs Deletion</li> <li>Two-sided Printing</li> <li>Watermark (predefined and custom)</li> <li>Xerox® Earth Smart Driver Settings</li> </ul> |              |               |               |
| Print from USB                              | <ul style="list-style-type: none"> <li>Allows walk-up printing from Type A USB port</li> <li>Supports direct printing from computer via Type B USB port</li> <li>Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</li> </ul>   |              |               |               |

# Xerox® VersaLink® C600 Color Printer

|  |  |
|--|--|
| <b>Operating Systems</b>   | Windows® 7, 8, 8.1, 10<br>Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016<br>macOS® 10.11, 10.12, 10.13<br>Citrix®<br>Redhat® Enterprise Linux®<br>Fedora Core<br>IBM® AIX®<br>HP-UX®<br>Oracle® Solaris<br>SUSE®<br>SAP®<br>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at <a href="http://www.support.xerox.com/en-gb">www.support.xerox.com/en-gb</a> . |
| <b>Fonts</b>   | PostScript fonts: 136<br>PCL fonts: 83   |
| <b>Xerox® Global Print Driver®</b>   | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end users, reducing the number of support calls and simplifying print services management.   |
| <b>Xerox® Pull Print Driver</b>  | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.   |
| <b>MOBILE SOLUTIONS AND MOBILE DEVICE APPS</b>                                 |  |
| <b>Apple® AirPrint®</b>  | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.  |
| <b>Mopria® Certified</b>   | ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.  |
| <b>Xerox® @printbyXerox</b>  | @printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® Printer or MFP using a single email address with no IT intervention. No training is needed. End users simply send attachments to the email address and release them at the panel on the MFP.  |
| <b>Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)</b> | The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.                           |
| <b>Xerox® Easy Assist App</b>  | The Xerox® Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox® Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly.                           |
| <b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>                       | Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.   |
| <b>SOFTWARE SOLUTIONS</b>  |  |
| <b>Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)</b>                | Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.   |

| SECURITY   |   |   |   |
|--|---|---|---|
| <b>Security Features</b>   | Access Controls<br>AES 256-bit encryption<br>Audit log<br>Certificate path validation<br>Certificate Revocation List (CRL)/Status Protocol (OCSP)<br>Cisco® Identity Services Engine (ISE) Integration<br>Detection of external program falsification (XCP plug-in)<br>Domain Filtering<br>FIPS 140-2<br>Firmware Verification<br>Immediate Disk Overwrite*<br>IP Address Filtering<br>IPsec<br>Network Authentication<br>Port Filtering<br>Pre-installed Self-Signed Certificates<br>Role Based Permissions<br>Secure Print<br>Security Certificate Management<br>Smart Card Enablement (CAC/PIV/.NET)<br>SNMPv3<br>Status Protocol (OCSP)<br>TLS 1.3/SSL<br>Trusted Platform Module (TPM)             |   |   |
|  | *Requires HDD/Productivity Kit  |   |   |
| ACCOUNTING   |   |   |   |
| XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)                                 |   |   |   |
| <b>Tracking</b>  | Print usage   |   |   |
| <b>Accounting</b>  | Xerox® Standard Accounting Tool<br>Up to 1,000 User Accounts without HDD<br>Up to 9,999 User Accounts with HDD<br>Up to 500 General Accounts<br><br>Network Accounting (Job-Based Accounting)<br>Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD<br>Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD<br>Up to 14,000 Accounting Records (transactions)  |   |   |
| <b>Features</b>  | <ul style="list-style-type: none"> <li>Administrator can manage the feature via the Embedded Web Server</li> </ul>  |   |   |
| ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING) |   |   |   |
|  | <ul style="list-style-type: none"> <li>Enhanced network accounting with up-to-the-minute data on how the system is being used</li> <li>Comprehensive management and enterprise-scale tracking and reporting of device usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.co.uk">www.xerox.co.uk</a></li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third-party server, enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third-party Networking Account</li> </ul> |   |   |
| PAPER HANDLING   |   |   |   |
| BYPASS TRAY  |   |   |   |
| <b>Capacity<sup>5</sup></b>  | 150 sheets  |   |   |
| <b>Sizes</b>   | Custom sizes: 76 x 127 mm to 216 x 356 mm   |   |   |
| <b>Weights</b><br>One-sided:<br>Two-sided:   | 60 to 220 gsm<br>60 to 176 gsm  |   |   |
| <b>Types</b>   | Bond<br>Plain Paper<br>Cardstock<br>Custom  | Envelopes<br>Hole Punched<br>Labels<br>Letterhead | Lightweight Card Stock<br>Pre-Printed<br>Recycled |

|   |  |  |  |
|---|--|--|--|
| <b>TRAY 1</b>   |  |  |  |
| <b>Capacity<sup>4</sup></b>   | 550 sheets                                 |  |  |
| <b>Sizes</b>  | Custom sizes: 76 x 190 mm to 216 x 356 mm  |  |  |
| <b>Weights</b><br>One-sided:<br>Two-sided:  | 60 to 220 gsm<br>60 to 176 gsm             |  |  |
| <b>Types</b>  | Bond<br>Plain Paper<br>Cardstock<br>Custom | Hole Punched<br>Labels<br>Letterhead<br>Lightweight Card Stock | Heavyweight Cardstock<br>Pre-Printed<br>Recycled |
| <b>UP TO 4 ADDITIONAL TRAYS</b>   |  |  |  |
| <b>Capacity<sup>5</sup></b>   | 550 sheets                                 |  |  |
| <b>Sizes</b>  | Custom sizes: 76 x 190 mm to 216 x 356 mm  |  |  |
| <b>Weights</b><br>One-sided:<br>Two-sided:  | 60 to 220 gsm<br>60 to 176 gsm             |  |  |
| <b>Types</b>  | Bond<br>Plain Paper<br>Cardstock<br>Custom | Hole Punched<br>Labels<br>Letterhead<br>Lightweight Card Stock | Heavyweight Cardstock<br>Pre-Printed<br>Recycled |
| <b>HIGH-CAPACITY FEEDER (ONLY ONE ADDITIONAL 550-SHEET TRAY CAN BE ADDED TO HIGH-CAPACITY FEEDER)</b> |  |  |  |
| <b>Capacity<sup>5</sup></b>   | 2,000 sheets                               |  |  |
| <b>Sizes</b>  | A4   |  |  |
| <b>Weights</b><br>One-sided:<br>Two-sided:  | 60 to 176 gsm<br>60 to 176 gsm             |  |  |
| <b>Types</b>  | Bond<br>Plain Paper<br>Hole Punched        | Letterhead<br>Lightweight Card Stock<br>Pre-Printed            | Recycled   |
| <b>TOTAL CAPACITY</b>   |  |  |  |
| <b>Standard Device Capacity<sup>5</sup></b>   | 700 sheets                                 |  |  |
| <b>Maximum Device Capacity<sup>5</sup></b>  | 3,250 sheets                               |  |  |
| <b>PAPER OUTPUT/FINISHING</b>   |  |  |  |
| <b>Capacity<sup>5</sup></b>   | Up to 500 sheets                           |  |  |
| <b>Automatic Two-sided Printing</b>   | Standard                                   |  |  |
| <b>FINISH</b>   |  |  |  |
| <b>Capacity<sup>5</sup></b>   | 500-sheet tray, 50-sheet stapling          |  |  |
| <b>MAILBOX</b>  |  |  |  |
| <b>Capacity<sup>5</sup></b>   | Four 100-sheet bins                        |  |  |

| DEVICE MANAGEMENT                                       |  |
|---|--|
| Network Protocols                                       | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD<br>LDAP<br>Bonjour®/AirPrint™<br>Most protocols not in use can be disabled  |
| Administrative Protocols                                | DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS   |
| REMOTE CONTROL PANEL                                    |  |
|   | <ul style="list-style-type: none"> <li>• Enables faster, more convenient technical support and user training</li> <li>• IT administrators and other authorised users can control the device remotely from a web page on any device</li> <li>• Remote user experience is identical to performing tasks directly at the device</li> </ul>  |
| XEROX® CENTREWARE® WEB SOFTWARE                         |  |
|   | <ul style="list-style-type: none"> <li>• A web-based server application for network administrators that permits web-browser-based device management from any workstation, whether running Windows, UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul> |
| XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE |  |
| Device Status   | <ul style="list-style-type: none"> <li>• Tray Status/Contents</li> <li>• Consumables Status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>   |
| Print Queue Viewing                                     | Job print queue management – view and delete   |
| Job Submission  | Print-ready files (PS, PCL, PDF, XPS, JPEG)  |
| Device Administration                                   | Allows simple, remote installation setting of configuration options and management of the device   |
| Browsers  | Microsoft® Internet Explorer®<br>Microsoft Edge™<br>Mozilla™ Firefox®<br>Apple® Safari®<br>Google Chrome™  |
| REMOTE SERVICES   |  |
| Automated Meter Readings (AMR)                          | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.   |
| Automatic Supplies Replenishment (ASR)                  | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.   |
| WHAT'S IN THE BOX                                       |  |
|   | VersaLink® C600 Colour Printer<br>Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 6,000 print capacity <sup>6</sup> , Black: 10,000 print capacity <sup>6</sup><br>Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers and Warranty Statement)<br>Installation Guide<br>Quick Use Guides<br>Power Cord  |

# Xerox® VersaLink® C600 Color Printer

| SUPPLIES AND ACCESSORIES                                       | QUANTITY   | PART NUMBER                                      |
|--|--|--|
| <b>SUPPLIES</b>  |  |  |
| <b>Standard Capacity Toner Cartridges</b>                      | Black: 6,000 standard pages <sup>6</sup><br>Cyan: 6,000 standard pages <sup>6</sup><br>Magenta: 6,000 standard pages <sup>6</sup><br>Yellow: 6,000 standard pages <sup>6</sup>     | 106R03899<br>106R03896<br>106R03897<br>106R03898 |
| <b>High-Capacity Toner Cartridges</b>                          | Black: 12,200 standard pages <sup>6</sup><br>Cyan: 10,100 standard pages <sup>6</sup><br>Magenta: 10,100 standard pages <sup>6</sup><br>Yellow: 10,100 standard pages <sup>6</sup> | 106R03907<br>106R03904<br>106R03905<br>106R03906 |
| <b>Extra-High Capacity Toner Cartridges</b>                    | Black: 16,900 standard pages <sup>6</sup><br>Cyan: 16,800 standard pages <sup>6</sup><br>Magenta: 16,800 standard pages <sup>6</sup><br>Yellow: 16,800 standard pages <sup>6</sup> | 106R03923<br>106R03920<br>106R03921<br>106R03922 |
| <b>ROUTINE MAINTENANCE ITEMS</b>                               |  |  |
| <b>Drum Cartridges</b>   | Cyan: 40,000 pages <sup>7</sup><br>Magenta: 40,000 pages <sup>7</sup><br>Yellow: 40,000 pages <sup>7</sup><br>Black: 40,000 pages <sup>7</sup>                                     | 108R01485<br>108R01486<br>108R01487<br>108R01488 |
| <b>Waste Cartridge</b>   | 30,000 pages <sup>7</sup>  | 108R01416  |
| <b>ACCESSORIES</b>   |  |  |
| <b>550-sheet Feeder</b>  |  | 097S04949  |
| <b>2,000-sheet High-Capacity Feeder (includes Caster Base)</b> |  | 097S04948  |
| <b>Stand (includes stabilisers)</b>                            |  | 097S04994  |
| <b>Caster Base</b>   |  | 097S04954  |
| <b>Finisher (500 sheets, 50-sheet stapler)</b>                 |  | 097S04952  |
| <b>4-Bin Mailbox (100 sheets per bin)</b>                      |  | 097S04953  |
| <b>Productivity Kit with 320 GB HDD</b>                        |  | 497K18360  |
| <b>Wireless Network Adapter (Wi-Fi Kit)</b>                    |  | 497K16750  |

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.

<sup>4</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

<sup>5</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Average standard pages. Declared yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme.

For more information, visit [www.xerox.co.uk/recycling](http://www.xerox.co.uk/recycling).

For more information, visit us at [www.xerox.co.uk/office](http://www.xerox.co.uk/office).

Configurations vary by geography.