

WorkCentre™ 7425 / 7428 / 7435 Colour Multifunction System



WorkCentre 7425 shown with Work Surface and Three Tray options.



WorkCentre 7428 shown with Work Surface, High-Capacity Tandem Tray and Office Finisher LX with Booklet Maker options.



WorkCentre 7435 shown with Work Surface, High-Capacity Tandem Tray and Professional Finisher options.

	WorkCentre 7425	WorkCentre 7428	WorkCentre 7435	
Output Speed – Printing ar	nd Copying			
Black and white	Up to 25 ppm (pages per minute) A4/210 x 297 mm LEF Up to 16 ppm 216 x 356 mm Up to 14 ppm A3/297 x 420 mm	Up to 28 ppm A4/210 x 297 mm LEF Up to 18 ppm 216 x 356 mm Up to 16 ppm A3/297 x 420 mm	Up to 35 ppm A4/210 x 297 mm LEF Up to 23 ppm 216 x 356 mm Up to 20 ppm A3/297 x 420 mm	
Colour	Up to 20 ppm A4/210 x 297 mm Up to 13 ppm 216 x 356 mm Up to 11 ppm A3/297 x 420 mm	Up to 28 ppm A4/210 x 297 mm Up to 18 ppm 216 x 356 mm Up to 16 ppm A3/297 x 420 mm	Up to 35 ppm A4/210 x 297 mm Up to 23 ppm 216 x 356 mm Up to 20 ppm A3/297 x 420 mm	
First-Page-Out Time				
Copy – Black and white	As fast as 6.7 seconds	As fast as 5.0 seconds	As fast as 5.0 seconds	
Copy – Colour	As fast as 8.7 seconds	As fast as 6.4 seconds	As fast as 6.4 seconds	
Paper Handling				
Paper Handling – Duplex A	utomatic Document Feeder			
Capacity	75 sheets (based on 80 gsm paper)			
Speed	50 images per minute black and whi	te/45 images per minute colour (A4 lo	ng edge feed (LEF))	
Sizes	A5/148 x 210 mm to A3/297 x 420 n	A5/148 x 210 mm to A3/297 x 420 mm		
Weights	60 to 120 gsm			
Paper Handling – Bypass T	ray			
Capacity ¹	100 sheets			
Sizes	A6/105 x 148 mm to SRA3/320 x 45	0 mm		
Weights	55 to 280 gsm			

Types

Same as front-loading trays plus envelopes

Capacity ¹	520 sheets
Sizes	User adjustable from 139.7 x 182 mm to A3/297 x 420 mm
Weights	60 to 280 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Gloss Heavyweight Gloss Extra Heavyweight Gloss Extra Heavyweight Gloss Labels Punched Letterhead Pre-printed
Envelope Tray (Optional	- replaces Tray 1)
Capacity ¹	Up to 60 envelopes
Sizes	DL, C5, C6
Weights	75 to 90 gsm
Paper Handling – Input 7	Tray Options - Three Tray Option
Tray 2, Tray 3, Tray 4	520 sheets each
Sizes	User adjustable from 139.7 x 182 mm to SRA3/320 x 450 mm
Weights	60 to 280 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Gloss Heavyweight Gloss Extra Heavyweight Gloss Labels Punched Letterhead Pre-printed Envelopes
Total Capacity ¹	2,180 sheets (Includes Tray 1, Three Tray option and Bypass Tray)
Paper Handling – Input 7	Tray Options - High-Capacity Tandem Tray Option
Tray 2	520 sheets
Sizes	User adjustable from 139.7 x 182 mm to SRA3/320 x 450 mm
Tray 3 and Tray 4	2,000 sheets total
Sizes	B5, A4

Weights	60 to 280 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Gloss Heavyweight Gloss Extra Heavyweight Gloss Extra Heavyweight Gloss Labels Punched Letterhead Pre-printed Envelopes
Total Capacity ¹	3,140 sheets (Includes Tray 1, High-Capacity Tandem Tray option and Bypass Tray)
Paper Handling – High-Cap	acity Feeder (HCF)
Capacity	2,000 sheets of 75 gsm
Sizes	A4/210 x 297 mm LEF, 184 x 266.7 mm LEF
Weights	55 to 216 gsm
Total Capacity ¹	5,140 sheets with High Capacity Tandem Tray option – 4,180 sheets with Three Tray option
Output – Standard	
Stacking Trays ¹	Dual Offset Catch Tray – up to 250 sheets each Face up Tray – up to 100 sheets
Sizes	A5/148 x 210 mm to SRA3/320 x 450 mm
Weights	60 to 256 gsm
Output – Integrated Office	Finisher Option
Stacking Tray	500 sheets of 80 gsm A4 or 250 sheets of 80 gsm A3
Sizes	B5 to A3
Weights	60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum less than 90 gsm or 2 sheets of 220 gsm covers) A3, A4, B4 and B5 sizes supported
Output – Office Finisher LX	Option
Stacking Tray	2,000 sheets unstapled or 1,000 sheets single staple or 750 sheets dual staple (90 gsm)
Sizes	B5 to A3
Weights	60 to 220 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum less than 90 gsm) A3, A4, B4 and B5 sizes supported
	nch for Office Finisher LX

2-hole punch 4-hole punch

 $^{^{\}rm 1}$ Paper capacities are based on 80 gsm stock; capacities will vary with different weight stocks.

Canacity	(O booklets (1.15 shoots per booklet 90 gem or less) 3.10 shoots per booklet giver 90 gem)
Capacity	40 booklets (1-15 sheets per booklet – 80 gsm or less; 2-10 sheets per booklet – over 80 gsm)
Sizes	A4/210 x 297 mm 216 x 356 mm A3/297 x 420 mm
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 55 to 90 gsm
Score/Crease	1-15 sheets / unstapled
Output – Professional Finis	sher Option
Top Tray	500 sheets
Stacking Stapling Tray	1,500 sheets
Sizes	B5 to SRA3
Weights	60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported
Booklets - Booklet Tray	Saddle-stitch up to 15 sheets (One 169 gsm cover plus fourteen 90 gsm sheets) V-fold up to 5 sheets SRA3, A4 supported
Hole Punch	2–4 Hole Punch, Swedish Hole Punch
Copy Specifications	
Document Scanner	Duplex Automatic Document Feeder with 75-sheet capacity (based on 80 gsm paper)
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scan, print, fax
Digital Imaging	Enhanced Gloss Level Auto colour Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation
	Variable zoom from 25 % to 400 % in 1 % increments

Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Auto colour selection Area Designation Poster mode Watermark Secure Watermark (requires Secure Watermark Kit option) Annotation Single/Dual colour Copy calibration Booklet creation Multi-up – 2, 4 or 8 up Repeat Image Transparency dividers Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Store and recall job programming Job interrupt Book copying Sample job Mixed-size originals Hole Punch (requires Professional Finisher or Office Finisher LX) V-Folding (requires Professional Finisher) Saddle-stitch booklets (requires Professional Finisher or Office Finisher LX) Stapling (single/dual/quad) (quad requires Professional Finisher) ID Card Copy
Foreign Device Interface	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Alliance Partner Programme
Print Specifications	
System	
Memory	1.5 GB
System Disk	Minimum 40 GB
Network Printing – Networ	k Controller
Processor	667 MHz
Printer Languages (auto sensing/switching)	Adobe® Postscript® 3™ (optional) TIFF PCL® 5c PS-PDF: v1.3 PCL® 6 HP-GL2™ XPS®
Network Printing – Resolut	ion

Print Engine: 1200 x 2400 dpi

Network Printing – Printing	g Features
Features	Enhanced Gloss Level Print Calibration Secure Print Delay Print (specific time) Sample Set Booklet creation Cover selection Inserts and exception pages Store File in Folder Paper selection by attribute N-up Saddle-stitch booklet making (requires Professional Finisher or Office Finisher LX) Hole Punch (requires Professional Finisher or Office Finisher LX) Booklet Fold / V Folding (requires Professional Finisher or Office Finisher LX) Watermark Secure Watermark (requires optional Secure Watermark Kit) Fit to new paper size Transparency Separators Banner Sheet enable/disable Output tray selection Image Quality Draft Mode Store and Recall driver settings Reduce/enlarge Mirror image Margins Bi-Directional status Two sided printing Scaling Overlays Print to Fax (requires optional Fax Kit)
Connectivity	Ethernet 10/100BaseTX High speed USB 2.0 printer port Wireless Ethernet (IEEE 802.11b) via third-party adapters Parallel Port (optional)
Operating Systems	Microsoft® XP® 32-bit, XP 64-bit, Windows Server 2003 32-bit, Windows Server 2003 64-bit, Windows Vista 32-bit, Windows Vista 64-bit Mac OS® 10.3 and above AIX 5Iv5.3 HP UX 11.0, 11i v2 Solaris 8, 9, 10 Linux® FedoraCore 1, 5 RedHat Enterprise Linux 4 SUSE 10.x
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6 Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI (All protocols not in use can be disabled)
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL
Fonts	Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 81 scalable fonts, line printer bitmap font

Printer Drivers	Environment	PCL5c and PCL 6	PostScript
Vista XPS (mini driver available)	Windows 2003/XP 32 Bit Windows 2003/XP 64 Bit Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit (Microsoft certified)	Bi-directional with user-selectable interface (standard ² and enhanced ³)	Bi-directional with user-selectable interface (standard ² and enhanced ³)
	Macintosh® OS 10.3.0 and above	N/A	Enhanced PPD file
	UNIX	N/A	Bi-directional with Xerox Custom Graphical User Interface
Xerox Mobile Express Driver (X-MED)	into a new network, and X-MED auto information. Save a list of "favourite" printer in any network, and greatly re • Printers are automatically discover • Printer list can be managed based	red	and provides status and capability cation print settings for use on any
Xerox Global Print Driver (X-GPD)	devices from a single driver. It provid of support calls, and simplifying print • Printers are automatically discover • Printer list can be managed based	red	or end-users, reducing the number
Print Submission Tools	Command prompt LPR/UNIX tool Contents Bridge tool supports TIFF	for print submission F/PDF/XPS and Office 2007 direct prin	t
Device Management			
Management Support	SNMP Version 1, SNMP Version 2c ar MIB access (IETF-MIB II RFC 1213), MIB RFC 2790, Printer MIB RFC 1759	Host Resources	
Xerox CentreWαre® Web	management from any workstatioWorks with any SNMP-managed p	y and installations, health checks and t	or any other operating system
IP Filter	Allows administrator to control print	access to device via IP address.	
Xerox CentreWαre® for Unicenter TNG®	 Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk 		
Xerox CentreWare® for Tivoli® Netware®	discovery performed by Tivoli Net\ • Provides the ability to see the discording Printers SmartSet	erox N-Series printers and WorkCentre /iew overed Xerox printers/devices in a Xero letView and Event Browser and Tivoli I	ox Printers Set in addition to the
Xerox CentreWare® for Microsoft Management Console (MMC)		nter discovery and management via a ver. It is a general-purpose managem	
Xerox CentreWαre® for HP® OpenView®	discovery performed by HP OpenV • Provides the ability to see the curre and IP Map via colour-coded icons	ent status of discovered Xerox printers s les to the OpenView alarm browser and	/devices under a Xerox PrinterMap

 $^{^2\,}S tandard: \,Driver\,based\,on\,Microsoft\,tree\,structure\,user\,interface\,(includes\,Xerox\,features\,and\,functionality)$

 $^{^{\}rm 3}$ Enhanced: Xerox custom graphical user interface

Xerox Device Manager	Xerox Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities
Xerox Device Types for SAP R/3 Environment Information available at www.xeroxofficesap solutions.com	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): • Simplex or duplex printing • Finishing – single or dual stapling • Tray pull location from any tray • Print security via PIN ID capability at the WorkCentre
Xerox SAP R/3 Intelligent Barcode Utility (Optional) Information available at www.xeroxofficesap solutions.com	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on SMart network controller Tray status/contents Consumables status
Xerox Barcode Pro PS Information available at www.xeroxofficesap solutions.com	Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
Smart eSolutions	
MeterAssistant	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. Device Direct or via client
CentreWare® Internet Serv	ices – Integrated Device Web Page
Device Status	Web server embedded on SMart Network Controller™ • Tray status/contents • Consumables status
Print Queue Viewing	Complete job print queue management – hold, release, promote and delete
Job Submission	Print-ready files (PS, PCL, TIFF, PDF, XPS) Output feature selection
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Windows® XP, Netscape Navigator®, Firefox® Microsoft® Internet Explorer Macintosh® 9.x/OS X: Netscape Navigator® 6.x, Apple® Safari™, Firefox® Linux: Netscape® 6.x
EFI Fiery® Network Control	ler (Optional)
Processor	1.86 GHz
Memory (ESS)	512 MB
System Disk	80 GB minimum
Print Languages (PDL)	PostScript 3

Features	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management
	Job Preview
	Job MergeChange Job Properties
	Pantone Colour Tables
	Expert Colour Settings: Profile, Rendering and Simulation
	ColorWise Pro Tools – calibration support, colour editor, profile manager FreeForm – Variable Data capabilities
	Booklet Maker 3.0 – booklet wizard to create booklets
	Print from USB flash drive Microsoft Office Doc conversion – print .doc, .xls, .ppt files without application
Connectivity	Ethernet 10/100/1000BaseTX
Optional	Hot folders and virtual printers
Optional	Impose 2.7 – imposition
	Paper Catalog
	Spot On Colour Management Auto Trapping
Fax Specifications	
Network Fax Server Inte	egration (Optional)
Fax Send Features	One-sided, two-sided, or two-sided rotate side 2
	Phone number entry
	Add to send list (50 numbers maximum)
	Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi)
	Original type (photo, text, or photo and text)
Fax Print Features	One- or two-sided printing
	Quantity Staple on/off
	Collate on/off
	Finisher output tray selection (top tray or main tray) Secure print on/off
Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Programme For details, visit www.xerox.com
Fax (Optional) – Standa	ard with One or Three Line Fax Option
	ITY (CCITT) group 3 quality/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi
Speed/Modem(s)	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
Speed/Compression	MH/G3, MMR/G4, JBig Super G3
Fax Send Features	Fax from print driver
	Auto fax transmission reduction
	Page-by-page job status at the machine Delay start
	Automatic memory resend
	Automatic cover sheets
	Priority send Broadcast
	Booklet Scan
	PSTN Fax
	Internet Fax LAN Fax
Fax Receive Features	One- or two-sided printing
	Reduction at reception to fit available paper
	Junk Fax prevention

Fax Forward	When enabled with the scan and fax kit, faxes can be received into a folder on the device hard drive. Images that are in the folder can be routed to an Email, an FTP or SMB location or a Fax.	
Fax Reports	Activity report Address Book Transmission confirmation Pending fax Folder List	
Fax Receive Mailboxes	Up to 200 password-protected folders	
Auto Dialing	Auto redial, Batch send	
Single Line option	Total of 200 speed dials (single-line option) Up to 50 dial groups with up to 20 recipients per group (single line option) Up to 200 dial groups with up to 200 recipients per group (with extended memory option)	
Internet Fax (Optional) – S	standard with One or Three Line Fax Option	
Capability	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents in black and white sent via email from remote Internet Fax machines or email clients	
Maximum Scan Area	A3	
Address Directory Access	Downloaded address list (comma-separated value file format)	
File Formats	TIFF-FX Profiles S with G3 MH, F with G4 MMR, or J with JBIG	
Resolutions	600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (black and white)	
Network Protocols	SMTP POP3	
Compliance	ITU-T T.37 compliant	
Scan Specifications		
Scanning (Optional)		
Capability	Colour Scanning, Greyscale, Black and White, Auto Colour	
Concurrency	Scan while the system is copying, printing or while it is transferring scan to network or fax jobs	
Input Speed	Scan at 50 ipm black and white/45 ipm colour (210 x 297 mm/A4 long edge feed)	
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1 bit (black and white), 8 bit (greyscale), 24 bit (colour)	
Maximum Scan Area	297 x 432 mm	
Secure Access and Authentication	Optional secure device login with network user name and password Supports: Kerberos (UNIX/Windows Server 2003), SMB (Windows Server 2003/Vista) LDAP	
Network Protocol	FTP via TCP/IP Microsoft SMB via TCP/IP Netware, HTTP and HTTPS	

File Formats	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF, PDF/A with MRC, JPEG, G3 MH, G4 MMR, MRC, JBIG 2 Huffman, JBIG Arithmetic Compression JPEG XPS Searchable PDF, PDF/A, XPS Password Protected PDF Encrypted PDF Linearised PDF
Document Management Fields	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard
Scan Features	Mixed size originals Bound originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview
Supported Scan Destinations (Varies by scanning software options purchased)	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop® (Professional and SE editions) SMARTsend® ScanFlowStore® Scan to Windows XP client SMB or FTP Scan to Folder Scan to Home
Scan to PC Desktop SE	 A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools ScanSoft PaperPort – image viewing and file management software ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.
Scαn to PC Desktop Pro	 A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools The PaperPort Personal Scanning Platform empowers office workers with the ability to customise, directly from the desktop, the scanning menus available to them on Xerox EIP enabled MFP devices. ScanSoft PaperPort Pro – image viewing and file management software ScanSoft OmniPage Pro (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox or through email WorkCentre to individual desktops. Also includes an Email inbox polling capability.
Scan to Email (Included wi	th the Scanning Option)
Capability	Colour scanning, Auto Colour, Greyscale, Black and White Direct document email from device Manual or directory Exchange/Notes/LDAP address searching
Network Protocol	SMTP, S/MIME, LDAP, LDAPs encoded
Authentication	Device login with network user name and password Supports: Kerberos (UNIX/Windows 2003 Server), SMB, (Windows 2003 Server) LDAP Domino
Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)

ges that are stored in the mailbox TP or SMB site via Job Flow Shee ges that are stored in the folder of are Print, NDS Authentication ove are Web Page via SSL are Watermark, Secure Access Unitediate or on demand, Encrypted	faxed directly to the device hard drive can then be printed, emailed, sensets. on the device hard drive can be viewed at the device hard drive can be viewed. The LDAP/Kerberos/SMB, Password if ied ID System® USB card reader, Scan to Email	
ire Print, NDS Authentication ove ire Web Page via SSL ire Watermark, Secure Access Uni ediate or on demand, Encrypted o-the-minute data on how the sy , copy and fax	er IP, LDAP/Kerberos/SMB, Password ified ID System® USB card reader, Scan to Email ystem is being used; comprehensive	I Protected PDF and Audit Log Encrypted Disk, Hard disk overwrite
ire Print, NDS Authentication ove ire Web Page via SSL ire Watermark, Secure Access Uni ediate or on demand, Encrypted o-the-minute data on how the sy , copy and fax	er IP, LDAP/Kerberos/SMB, Password ified ID System® USB card reader, Scan to Email ystem is being used; comprehensive	I Protected PDF and Audit Log Encrypted Disk, Hard disk overwrite
re Web Page via SSL re Watermark, Secure Access University ediate or on demand, Encrypted o-the-minute data on how the sy , copy and fax trols and tracks black and colour of	ified ID System® USB card reader, Scan to Email /stem is being used; comprehensive	Encrypted Disk, Hard disk overwrite
re Web Page via SSL re Watermark, Secure Access University ediate or on demand, Encrypted o-the-minute data on how the sy , copy and fax trols and tracks black and colour of	ified ID System® USB card reader, Scan to Email /stem is being used; comprehensive	Encrypted Disk, Hard disk overwrite
re Web Page via SSL re Watermark, Secure Access University ediate or on demand, Encrypted o-the-minute data on how the sy , copy and fax trols and tracks black and colour of	ified ID System® USB card reader, Scan to Email /stem is being used; comprehensive	Encrypted Disk, Hard disk overwrite
ediate or on demand, Encrypted o-the-minute data on how the sy , copy and fax crols and tracks black and colour o	Scan to Émail /stem is being used; comprehensive	
, copy and fax crols and tracks black and colour (e usage tracking and reporting; print,
, copy and fax crols and tracks black and colour (e usage tracking and reporting; print,
	copy, print, fax and scan usage	
x Standard Accounting		
based accounting d-party integration ports Foreign Device Interface ve directory user profile – Control x Page Accountant : Audit 5	s colour copy and print usage	
counting		
y, Print, Fax and Scan usage		
o 9,999 User accounts (User ID)		
Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.		
WorkCentre 7425	WorkCentre 7428	WorkCentre 7435
00	80,000	105,000
	Audit 5 counting r, Print, Fax and Scan usage o 9,999 User accounts (User ID) ble/disable via the web UI or the can be exported via a CSV file, similar to secure print. WorkCentre 7425	Audit 5 counting r, Print, Fax and Scan usage o 9,999 User accounts (User ID) ole/disable via the web UI or the GUI in tools, admin can manage the can be exported via a CSV file, user required to enter XSA ID into the similar to secure print. WorkCentre 7425 WorkCentre 7428

Accessories

Three Tray Module

High Capacity Tandem Tray

High Capacity Feeder

Envelope Tray

Integrated Office Finisher

Office Finisher LX

Booklet Maker (requires Office Finisher LX)

Professional Finisher

2/4 Hole Punch (Office Finisher)

1500-sheet Professional Finisher with 50-sheet Stapling

Swedish 4 Hole Punch (Professional Finisher only)

Convenience Stapler

Work Surface

One-line fax with Internet Fax

Three-line fax with Internet Fax

Fax Server Enablement

Thumbnail preview

Foreign Device Interface Kit

Secure Watermark

Scan to PC Desktop (Professional or SE edition)

Media Print (Print from a USB Thumb drive or media card)

Parallel Port Printing

Network Scanning

Network Accounting Kit

Security Kit

Postscript Kit

USB Media cable Kit

USB Media Reader Kit

Mobility Plate

EFI Controller

Secure Access

SMARTSend

Electrical Requirements

220-240 V Nominal, 50/60 Hz, 10A

Power Consumption				
Running	< 646 watts			
	- 0-10 Wallis			
Standby	< 145 watts			
Low-Power Mode	< 79 watts			
Sleep Mode	< 2 watts			
Warm Up	45 seconds (maximum)			
Low-Power Recovery	30 seconds (maximum)			
Required Temperature Range	10° to 28° C			
Required Relative Humidity	15% to 85%			
Noise Emission	20 dB(A) standby 56 dB(A) running			
Heat Emission	2584 BTU/Hr running 580 BTU/Hr standby			

Dimensions and Weights	Width	Depth	Height	Weight	
Base Unit	1046 mm	678 mm	1125 mm	144 kg	
Xerox Extensible Interface	Platform® (EIP)				
	Xerox EIP is a software platform inside the WorkCentre 7425/7428/7435 that enables personalised solutions you can access right from the device touch screen. These applications can leverage your existing databases and meet your specific business challenges.				
Certifications	'				
	EnergyStar 89/336/EEC (Europe) TUV Listed CB Certified (IEC 60950-1/EN 60950-1) 73/23/EEC (Europe) Novell Tested and Approved Windows Hardware Quality Labs Blue Angel Certified				
Supplies	Description		Ord	ler Number	
Toner Cartridges	Black Toner Cartridge -	Metered	006	5R01391	
	Yellow Toner Cartridge	- Metered	006	5R01392	
	Magenta Toner Cartrid	lge - Metered	006	5R01393	
	Cyan Toner Cartridge -	Metered	006	5R01394	
Staple Refills	Integrated Office Finis	her	000	BR12941	
	Office Finisher LX		300	BR12941	
	Professional Finisher		300	BR12941	
Staple Cartridges	Integrated Office Finis	her	300	BR12964	
	Office Finisher LX		300	BR12964	
	Professional Finisher		300	BR12964	
	Booklet Maker for Offic	ce Finisher LX	300	BR12897	
	Booklet Maker for Professional Finisher		300	BR12925	
SMart Kits	Description		Ord	ler Number	
	SMart Kit® Drum Cartr	idge	013	BR00647	
	SMart Kit® Waste Cart	ridge	300	BR13061	
	SMart Kit® Fuser Modu	ıle (220 V)	300	BR13063	
	Intermediate Belt Tran	ısfer (IBT) Cleaner	001	IR00600	



008R13064















Belt Transfer Roller